+44 (0) 1903 205 532



VTHT20-80

High Temperature Silicone Rubber

General Information

A high temperature rated compound with good mechanical properties. This compound has a natural off-white colour and accepts limited pigments, most commonly red oxide or grey.

Material compliance

FDA compliant to 21 CFR 177.2600

Environmental Resistance

Silicone Rubber products have an excellent resistance to:

Ozone

Cosmic radiation

Weathering in general

Oxidation

Ionising radiation

Ultraviolet Light

Corona Discharge

Material Properties

Cure conditions: 1.5% (50% paste of bis (2,4-dichlorobenzoyl)-peroxide in silicone fluid), 10 min / 135°C in press, post-cured 4h / 200°C.

Property			Test Method						
	Units	VTHT20	VTHT30	VTHT40	VTHT50	VTHT60	VTHT70	VTHT80	
Appearance	-	Off-White							-
Temperature Range	°C	-50 to +300 (max)							-
Density	g/cm ³	1.11	1.10	1.12	1.15	1.15	1.18	1.20	ISO 1183-1 A
Hardness	° Shore A	24	32	42	52	61	70	79	DIN 53505
Tensile strength	N/mm ²	9.0	9.0	10.0	11.0	11.0	11.0	10.0	DIN 53501 S1 / ISO 27
Elongation at break	%	920	720	580	520	440	440	420	DIN 53504 S 1
Tear strength	N/mm	26	23	23	25	24	26	26	ASTM D 624 B
Rebound Resilience	%	42	52	56	56	57	53	53	DIN 53512
Compression Set	%	33	36	36	34	31	40	57	DIN ISO815-B (22hrs at 175°C)

These figures are only intended as a guide and should not be used in preparing specifications. Size tolerance to ISO 3302-1: 2014.

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for their intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. The information contained within this data sheet is subject to change without notice.

Viking Extrusions Ltd – Ivy Arch Road, Worthing, West Sussex, BN14 8BX, UK

Company Number: 2634482UK VAT Number: GB587651394 Registered in England & Wales

REV 03 - Last Updated: 16/01/25



ISO 14001 Environmental Management

FM 40230

EMS 769212